

Thermoplastic Valves



Asahi/America valve and actuation products have a three-year product warranty. Scan the QR code or visit our website at asahi-america.com/support/warranty-policy for full terms and conditions.

Type-21/21a Ball Valves

Sizes: 1/2" - 6"

Models (PVC & CPVC): Socket, threaded, flanged (ANSI)

Models (PP & PVDF): IPS or metric (DIN) socket, threaded, butt, flanged (ANSI)

Bodies: PVC, CPVC, PP, PVDF

Seats: PTFE backed with EPDM or FKM

Seals: EPDM, FKM

NSF-61 Certified

(1/2" - 4" PVC/CPVC/EPDM/FKM)



Type-23 Multiport™ Ball Valves

Sizes: 1/2" - 6"

Models (PVC & CPVC): Socket, threaded, flanged (ANSI)

Models (PP & PVDF): IPS or metric (DIN) socket, threaded, butt, flanged (ANSI)

Bodies: PVC, CPVC, PP, PVDF

Seats: PTFE backed with EPDM or FKM

Seals: EPDM, FKM

NSF-61 Certified

(1/2" - 4" PVC/EPDM/FKM)



Type-21a SST Flow Control Ball Valves

Sizes: 1/2" - 2"

Models: Socket, threaded, flanged (ANSI)

Body: PVC

Seats: PTFE backed with EPDM or FKM

Seals: EPDM, FKM



Omni® Type-27 Ball Valves

Sizes: 3/8" - 2"

Models: Socket, threaded

Bodies: PVC, CPVC

Seat: PTFE backed with EPDM

Seal: EPDM

NSF-61 Certified

(3/8" - 2" PVC/EPDM)



Ball Check Valves

Sizes (True Union): 1/2" - 2"

Sizes (Single Union): 3" - 4"

Models (PVC & CPVC): Socket, threaded, flanged (ANSI)

Models (PP & PVDF): IPS or metric (DIN) socket, threaded butt flanged

Bodies: PVC, CPVC, PP, PVDF

Seats: EPDM, FKM, PTFE

Seals: EPDM, FKM, PTFE

Options: Foot valve screen and stainless steel springs



NSF-61 Certified

(1/2" - 4" PVC/CPVC/EPDM/FKM)

Gate Valves

Sizes: 1-1/2" - 14"

Body: HI-PVC

Model: Flanged (ANSI)

Type: Non-rising stem

Seals: EPDM or FKM



NSF-61 Certified

(1-1/2" - 14" PVC/PP/EPDM/FKM)

Type-14 True Union Diaphragm Valves

Sizes: 1/2" - 2"

Bodies: PVC, CPVC, PP, PVDF

Bonnet: PVC, PP, PPG, PVDF

End Connectors (PVC & CPVC):

IPS socket or threaded

End Connectors (PP & PVDF):

IPS or metric (DIN) socket, threaded, butt

Diaphragms: EPDM, three-layer EPDM/PVDF/PTFE; also available in nitrile and FKM



NSF-61 Certified

(1/2" - 2" PVC/CPVC/EPDM/PTFE)

Swing Check Valves

Sizes: 3/4" - 8"

Model: Flanged (ANSI)

Bodies: HI-PVC, PP, PVDF

Seats: EPDM, FKM, PTFE

Options: Lever and weight stainless steel springs



Labcock® Ball Valves

Size: 1/4"

Bodies: PVC

Models: Male thread x male thread, male thread x hose (OD 0.375"), male thread x female thread, male thread x hose, hose x hose, female thread x female thread, male thread elbow (OD 0.63") 90°

Seats: EPDM

Seals: EPDM



NSF-61 Certified

(1/4" PVC/EPDM)

Globe Valves

Sizes: 1/2" - 4"

Bodies: PVC, PP

Model (Flanged): 1/2" - 4" (ANSI) (PVC and PP)

Model (Socket or Threaded): 1/2" - 2" (PVC), 1/2" - 1" (PP)

Seals: EPDM or FKM



Flanged Diaphragm Valves

Sizes: 1/2" - 10"

Bodies: PVC, CPVC, PP, PVDF

Bonnet: PVC, PP, PPG, PVDF

End Connectors: Flanged

Diaphragms: EPDM, three-layer EPDM/PVDF/PTFE; also available in nitrile and FKM

NSF-61 Certified

(1/2" - 4" PVC/CPVC/EPDM/PTFE)



Constant Flow Valves

Sizes: 1/2", 3/4", 1", 2", 3" and 4"

Body: PVC

Bonnet: PVC

Model: Flanged (ANSI)

Seals: EPDM

Springs: 304 Stainless steel with PTFE coating

