



T-621G

Threaded x MIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
201-003G	1/2"	100	10	50
201-004G	3/4"	100	10	56

- Dezincification Resistant Brass Alloy
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



T-622G

Threaded x FIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
201-103G	1/2"	100	10	46
201-104G	3/4"	100	10	51

- Dezincification Resistant Brass Alloy
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



P-623G

Press x FIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
201-133G	1/2"	100	10	45
201-134G	3/4"	100	10	48

- Dezincification Resistant Brass Alloy
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- Wetted Surfaces Contain Less than .25% Lead Content





T-624G

Crimp Pex Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
201-123G	1/2"	96	6	53

- Dezincification Resistant Brass Alloy
- IAPMO Certified - NSF 61 & ANSI 372
- Wetted Surfaces Contain Less than .25% Lead Content





T-621

Threaded x MIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
201-003	1/2"	100	10	53
201-004	3/4"	100	10	57

- Residential and Commercial Applications
- 3/4" Hose Thread Outlet





T-641G
Threaded x FIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
202-003G	1/2"	100	10	58
202-004G	3/4"	100	10	64

- Dezincification Resistant Brass Alloy
- 3/4" Hose Thread Outlet
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



CERTIFIED
LEAD FREE

NSF/ANSI/CAN 61 & 372



S-641G
Solder x FIP Connection, 125 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
202-103G	1/2"	100	10	59
202-104G	3/4"	100	10	65

- Dezincification Resistant Brass Alloy
- 3/4" Hose Thread Outlet
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



CERTIFIED
LEAD FREE

NSF/ANSI/CAN 61 & 372

