



T-511G

Swing, Y-Pattern, Threaded Connection, 300 WOG, Class 150



CERTIFIED
LEAD FREE

NSF/ANSI/CAN 61 & 372

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-303G	1/2"	60	10	34
105-304G	3/4"	40	10	36
105-305G	1"	30	10	40
105-306G	1-1/4"	20	5	39
105-307G	1-1/2"	16	4	41
105-308G	2"	8	2	32

- Dezincification Resistant Bronze
- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



S-511G

Swing, Y-Pattern, Solder Connection, 300 WOG, Class 150



CERTIFIED
LEAD FREE

NSF/ANSI/CAN 61 & 372

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-403G	1/2"	60	10	31
105-404G	3/4"	40	10	36
105-405G	1"	30	10	41
105-406G	1-1/4"	20	5	41
105-407G	1-1/2"	16	4	41
105-408G	2"	8	2	34

- Dezincification Resistant Bronze
- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content





T-521G

Inline, Threaded Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-603G	1/2"	100	25	33
105-604G	3/4"	128	16	52
105-605G	1"	96	12	62
105-606G	1-1/4"	36	9	39
105-607G	1-1/2"	32	8	38
105-608G	2"	16	4	36

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



S-521G

Inline, Solder Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-613G	1/2"	100	25	33
105-614G	3/4"	128	16	54
105-615G	1"	96	12	60
105-616G	1-1/4"	48	6	52
105-617G	1-1/2"	32	4	40
105-618G	2"	16	2	42

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



P-521G

Inline, Press Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-623G	1/2"	120	20	35
105-624G	3/4"	96	8	42
105-625G	1"	68	17	36
105-626G	1-1/4"	32	4	31
105-627G	1-1/2"	24	3	38
105-628G	2"	18	3	40

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- ASME B16.51
- Wetted Surfaces Contain Less than .25% Lead Content



E-521G

Inline, Expansion Pex Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-633G	1/2"	80	20	33
105-634G	3/4"	80	20	33
105-635G	1"	72	18	33

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- ASTM F1960
- Wetted Surfaces Contain Less than .25% Lead Content





T-501G

Horizontal Swing, Threaded Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-103G	1/2"	120	10	54
105-104G	3/4"	100	10	47
105-105G	1"	72	6	60
105-106G	1-1/4"	60	5	59
105-107G	1-1/2"	32	4	54
105-108G	2"	20	2	55
105-109G	2-1/2"	12	2	58
105-110G	3"	6	1	43
105-111G	4"	4	1	43

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



S-501G

Horizontal Swing, Solder Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-203G	1/2"	120	10	48
105-204G	3/4"	100	10	60
105-205G	1"	72	6	63
105-206G	1-1/4"	40	5	59
105-207G	1-1/2"	32	4	57
105-208G	2"	24	2	70
105-209G	2-1/2"	10	1	48
105-210G	3"	8	1	54

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



P-501G

Horizontal Swing, Press Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-003G	1/2"	160	10	68
105-004G	3/4"	120	10	77
105-005G	1"	60	5	51
105-006G	1-1/4"	40	5	45
105-007G	1-1/2"	30	5	53
105-008G	2"	24	2	62

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- One-Piece Body Design
- Heavy Pattern Cast Brass Construction
- EPDM O-Ring Seal
- Metal-to-Metal Disc Seal
- Truesdail Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content





T-511

Swing, Y-Pattern, Threaded Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-303	1/2"	60	10	62
105-304	3/4"	40	10	37
105-305	1"	30	10	40
105-306	1-1/4"	20	5	39
105-307	1-1/2"	16	4	43
105-308	2"	8	2	33
105-309	2-1/2"	6	1	55
105-310	3"	4	1	49

- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Buy American Act Compliant: 2-1/2" - 3"



S-511

Swing, Y-Pattern, Solder Connection, 300 WOG, Class 150

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-403	1/2"	60	10	36
105-404	3/4"	40	10	35
105-405	1"	30	10	38
105-406	1-1/4"	20	5	44
105-407	1-1/2"	16	4	43
105-408	2"	8	2	34
105-409	2-1/2"	6	1	49
105-410	3"	4	1	47

- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Buy American Act Compliant: 2-1/2" - 3"



**T-501**

Horizontal Swing, Threaded Connection, 200 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-103	1/2"	120	10	53
105-104	3/4"	100	10	59
105-105	1"	72	6	60
105-106	1-1/4"	40	5	59
105-107	1-1/2"	32	4	54
105-108	2"	24	2	56
105-109	2-1/2"	12	2	57
105-110	3"	6	1	42
105-111	4"	4	1	44

- Residential and Commercial Applications

**S-501**

Horizontal Swing, Solder Connection, 200 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-203	1/2"	120	15	47
105-204	3/4"	100	10	57
105-205	1"	72	6	59
105-206	1-1/4"	32	5	52
105-207	1-1/2"	32	4	54
105-208	2"	20	2	58

- Residential and Commercial Applications

**T-550**

Stainless Steel, Swing, Threaded Connection, 200 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-803	1/2"	66	1	71
105-804	3/4"	48	1	1
105-805	1"	30	1	1
105-806	1-1/4"	24	1	2
105-807	1-1/2"	14	1	3
105-808	2"	4	1	5

- One-Piece Body Design
- Heavy Pattern Body
- PTFE O-Ring Seal
- Metal-to-Metal Disc Seal





F-571

Horizontal Swing, Bolted Bonnet, Class 125

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-725	2-1/2"	1	1	24
105-703	3"	1	1	44
105-704	4"	1	1	78
105-706	6"	1	1	152
105-708	8"	1	1	259
105-710	10"	1	1	417
105-712	12"	1	1	615

- Bonnet & Disc
- Lead Free Bronze Seat Ring
- Pressure Rating: Class 125
- Conforms to MSS SP-71
- Flange: ASME B16.1
- Face-to-Face: ANSI/ASME B16.10
- Lead Free Compliant

✓ LEAD FREE



F-591

Wafer Style, Double Door, Aluminum Bronze Disc, Class 125

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-925	2-1/2"	1	1	5
105-903	3"	1	1	8
105-904	4"	1	1	9
105-906	6"	1	1	20
105-908	8"	1	1	33
105-910	10"	1	1	56
105-912	12"	1	1	90

- Aluminum Bronze Disc
- Stainless Steel Stem
- Pressure Rating: Class 125
- Lead Free Compliant

✓ LEAD FREE



F-592

Ductile Iron, Wafer Style, Dual-Plate, Stainless Steel Disc, Class 125

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-525	2-1/2"	1	1	5
105-503	3"	1	1	7
105-504	4"	1	1	9
105-506	6"	1	1	21
105-508	8"	1	1	39
105-510	10"	1	1	66
105-512	12"	1	1	97

- Stainless Steel Disc
- Two Torsion Springs Activate Each Set of Valve Plates
- Quick-Close Action Prevents the Medium Flowing Back
- Easy Installation onto Either Vertical or Horizontal Pipeline

