

T-598NL**No Lead Forged Brass
1/4-Turn Ball-Type Dual Handle
Angle Stop Valve**

Third-party tested and certified;
NSF/ANSI 61
125 CWP

T-598NL Angle
OD x OD x ODT-598NL Angle
F1807 x OD x ODT-598NL Angle
F1960 x OD x ODT-598NL Straight
OD x OD x ODT-598NL Straight
F1807 x OD x ODT-598NL Straight
F1960 x OD x OD**T-598NL OD x OD x OD Angle Stop**

114-630NL	5/8" x 3/8" x 1/4"	Comp. (OD) x Comp. (OD)	T-598NL	100	10
114-631NL	5/8" x 3/8" x 3/8"	Comp. (OD) x Comp. (OD)	T-598NL	100	10

T-598NL F1807 x OD x OD Angle Stop

114-632NL	1/2" x 3/8" x 3/8"	PEX (F1807) x Comp. (OD)	T-598NL	120	5
114-633NL	1/2" x 3/8" x 1/4"	PEX (F1807) x Comp. (OD)	T-598NL	100	10

T-598NL F1960 x OD x OD Angle Stop

114-634NL	1/2" x 3/8" x 3/8"	PEX (F1960) x Comp. (OD)	T-598NL	100	10
114-635NL	1/2" x 3/8" x 1/4"	PEX (F1960) x Comp. (OD)	T-598NL	100	10

T-598NL OD x OD x OD Straight Stop

114-730NL	5/8" x 3/8" x 1/4"	Comp. (OD) x Comp. (OD)	T-598NL	100	10
114-731NL	5/8" x 3/8" x 3/8"	Comp. (OD) x Comp. (OD)	T-598NL	100	10

T-598NL F1807 x OD x OD Straight Stop

114-732NL	1/2" x 3/8" x 3/8"	PEX (F1807) x Comp. (OD)	T-598NL	120	10
114-733NL	1/2" x 3/8" x 1/4"	PEX (F1807) x Comp. (OD)	T-598NL	100	10

T-598NL OD x OD x OD Straight Stop

114-734NL	1/2" x 3/8" x 3/8"	PEX (F1960) x Comp. (OD)	T-598NL	100	10
114-735NL	1/2" x 3/8" x 1/4"	PEX (F1960) x Comp. (OD)	T-598NL	100	10

Backflow Preventers**T-459 / S-459 / P-459****Forged Brass Backflow
Preventer with Atmospheric
Vent**

Third-party tested and certified;
ASSE 1012,
CSA B64.3
175 psi @ 210°F



T-459

P-459

115-113	1/2"	FNPT x FNPT	T-459	25	1
115-114	3/4"	FNPT x FNPT	T-459	25	1
115-117	1/2"	Sweat x Sweat	S-459	25	1
115-118	3/4"	Sweat x Sweat	S-459	25	1
115-112	3/4"	Press x Press	P-459	18	1

Certifications	Part No.	Size	Configuration	Model	Cs.	Ct.
T-457 No Lead Forged Brass Backflow Preventer Third-party tested and certified; ANSI/NSF 61 (NL only) ASSE 1024 CSA B64.6 150 psi @ 180°F Min operating pressure 10 psi	115-103NL	1/2"	FNPT x FNPT	T-457NL	25	1
	115-104NL	3/4"	FNPT x FNPT	T-457NL	25	1
	115-105NL	1"	FNPT x FNPT	T-457NL	25	1



Pressure Relief Valves

T-50NL

No Lead Forged Brass Adjustable Pressure Relief Valve

Third-party tested and certified;
 NSF/ANSI 61
 150 CWP



T-50NL Adjustable PRV (75-150 PSI) Factory Set at 75 PSI

111-302NL	1/2"	MNPT x FNPT	T-50NL	120	10
111-304NL	3/4"	MNPT x FNPT	T-50NL	120	10

T-50NL Adjustable PRV (75-150 PSI) Factory Set at 100 PSI

111-303NL	1/2"	MNPT x FNPT	T-50NL	120	10
111-305NL	3/4"	MNPT x FNPT	T-50NL	120	10

Vacuum Breakers

T-553NL

No Lead Forged Brass Automatic Vacuum Breaker

Third-party tested and certified;
 ANSI/NSF 372 (NL only)
 ASSE 1011
 125 CWP
 Max temp 180°F



T-553NL

107-194	3/4"	FGHT x MGHT	T-553	200	20
107-194NL	3/4"	FGHT x MGHT	T-553NL	200	20

T-553CNL Chrome-Plated

107-195	3/4"	FGHT x MGHT	T-553C	200	20
107-195NL	3/4"	FGHT x MGHT	T-553CNL	200	20

Certifications	Part No.	Size	Configuration	Model	Cs.	Ct.					
T-554 Forged Brass Manual Vacuum Breaker 125 CWP Max temp 180°F	107-196	3/4"	FGHT x MGHT	T-554	200	20					
											
T-555 Nylon Resin Automatic Hose Bibb Vacuum Breaker 125 CWP Max temp 180°F	107-197	3/4"	FGHT x MGHT	T-555	300	30					
											
T-557 Forged Brass Self-Draining Vacuum Breaker Third-party tested and certified; ASSE 1011 125 CWP Max temp 180°F	T-557	3/4"	FGHT x MGHT	T-557	100	10					
	107-193										
	T-557C Chrome-Plated	3/4"	FGHT x MGHT	T-557C	100	10					
	107-199										
											
											
T-557C											
T-557											