



T2™ TECHNOLOGY HACKSAW BLADES

T2™ TECHNOLOGY

Blade design delivers up to 2X longer blade life versus the prior generation of LENOX hacksaw blades

SHATTER RESISTANT

Bi-Metal construction allows blades to bend and flex without breaking



TPI	LENGTH X WIDTH		1-PACK	2-PACK	10-PACK	100-PACK	APPLICATION
	IN	MM	PROD NO	PROD NO	PROD NO	PROD NO	
14	12 X 1/2	300 X 12.7	—	—	20143V214HE	—	Wood and Metal
18	10 X 1/2	254 X 12.7	—	20163T018HE	20140V018HE	—	Heavy Metal
18	12 X 1/2	300 X 12.7	20154S218HE	20160T218HE	20144V218HE	20116218HE	Heavy Metal
24	10 X 1/2	254 X 12.7	20151S024HE	23930T024HE	20141V024HE	20111024HE	Medium Metal
24	12 X 1/2	300 X 12.7	20155S224HE	20161T224HE	20145V224HE	20117224HE	Medium Metal
32	10 X 1/2	254 X 12.7	—	20164T032HE	20142V032HE	—	Thin Metal
32	12 X 1/2	300 X 12.7	20156S232HE	20162T232HE	20146V232HE	20118232HE	Thin Metal

HIGH TENSION HACKSAW

50,000 PSI

HIGH BLADE TENSION

Unique I-Beam construction allows blade to tension up to 50,000 psi, resulting in fast, straight cuts

COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in wet or cold environments

CONVERT TO A JAB SAW

Accepts any LENOX reciprocating saw blade to be used as a jab saw

CONVENIENT BLADE STORAGE

Store up to 5 extra 12" hacksaw blades in the I-Frame



Tensioning Mechanism



Use as a Jab Saw



Stores up to 5 Blades in I-Frame



Comfortable Grips

PROD NO	BLADE SPECIFICATION
12132HT50	12" (305 mm) 24TPI Hacksaw Blade

LOW PROFILE HACKSAW

40,000 PSI

HIGH TENSION

Allows blade to tension up to 40,000 PSI, resulting in fast, straight cuts


FITS INTO TIGHT SPOTS

Low profile tip easily handles close-quarter cuts

MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
209205012	12" (305 mm) 24TPI Hacksaw Blade



Flush Cutting

LIGHTWEIGHT HACKSAW

30,000 PSI

HIGH TENSION

Saw will tension up to 30,000 PSI

ERGONOMIC GRIP

Front handle grip helps reduce fatigue in continuous cutting applications

MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
1213188300	12" (305 mm) 24TPI Hacksaw Blade



Flush Cutting



Comfortable Grips

COMPACT HACKSAW

20,000 PSI

ADJUSTABLE TENSION

Lightweight aluminum beam achieves tension up to 20,000 PSI

DURABLE GRIP

Long lasting metal handle

MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
1805722	12" (305 mm) 24TPI Hacksaw Blade



Durable Grip



ADJUSTABLE HACKSAW

15,000 PSI

EASILY ADJUST TENSION

Large front tensioning mechanism is easy to hold and adjust up to 15,000 PSI

ERGONOMIC GRIP

Rubberized grip allows for confident handling in any work environment

ADJUSTABLE FRAME

Frame will accept both 10" and 12" Hacksaw Blades

PROD NO	BLADE SPECIFICATION
1805723	12" (305 mm) 24TPI Hacksaw Blade



Comfortable Grip

LIGHT DUTY HACKSAW

12,000 PSI

ADJUSTABLE TENSION

Lightweight aluminum beam achieves tension up to 12,000 PSI

ROBUST TENSIONING MECHANISM

Keeps parts in place when changing the blade

ERGONOMIC GRIP

Durable handle enables a confident grip in most work environments

MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
1884466	12" (305 mm) 24TPI Hacksaw Blade



Comfortable Grip

MINI HACKSAW

FITS INTO TIGHT SPACES

COMFORTABLE GRIP

Ergonomic handle design for comfort

TOOL FREE BLADE CHANGE

Toolless blade change design reduces down time

FITS INTO TIGHT SPOTS

Adjustable blade length for flush cutting applications

ADDED VERSATILITY

Accepts both 10" and 12" hacksaw blades or any length of reciprocating saw blade

PROD NO	BLADE SPECIFICATION
LX2014041	10" (254 mm) 24TPI Hacksaw Blade



PLASTIC PIPE HAND SAW

PVC/ABS

CUTS PLASTIC PIPE EASILY

Cutting teeth cut on the pull stroke and not on the push stroke for safety

COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in cold, hot, wet or dirty environments

FLUSH CUTTING OPTION

Easily mount the blade on the bottom of handle for flush cutting applications



TPI	LENGTH		PROD NO	DESCRIPTION
	IN	MM		
10	12	305	20985HSF12	12" Blade & Handle
10	18	457	20980HSF18	18" Blade & Handle
10	12	304	20982HSB12	12" Replacement Blade
10	18	457	20981HSB18	18" Replacement Blade



Comfortable Handle



One Step Flush Cuttings

FOLDING JAB AND UTILITY SAW

DESIGNED FOR CUTTING MULTIPLE MATERIALS

COMFORTABLE GRIP

Over-molded rubberized grip for a comfortable and secure grip while working

SECURELY HOLDS BLADE

Aluminum locking mechanism helps prevent blade from being removed during use

ACCOMMODATES HACKSAW BLADE

Ideal for flush cutting applications or when a hacksaw is not available



Rotate Blade Out



Loosen Knob to Change Blade

PROD NO	DESCRIPTION	BLADES INCLUDED	APPLICATION
20997TFHS618636	Folding Jab Saw with 2 Blades	635R and 6J6R	Plaster, drywall, wood, plastic and metal cutting
148216J6R	1pk Replacement Blades		

COMPACT HAND HACKSAW

CLOSE QUARTER™ SAW

Cut a Wide Variety in Tight Spaces

RUGGED DESIGN

Heavy duty aluminum handle

FITS IN TIGHT SPOTS

Allows for flush cutting applications

PROD NO	DESCRIPTION	TPI	BLADE LENGTH	
			IN	MM
20975975	Compact Hand Saw	24	10	254
20908908	Close Quarter™ Saw	32	6	152
20906906	10pk Replacement Blades	32	6	152



20975975



20908908