



SPECIALTY

TPI	LENGTH		PROD NO	SHAPE	MILWAUKEE®	DIABLO®	MK MORSE®
	IN	MM					
10	6	152	6110R		4172, 5712	DS0608BFD5, DS0608CF3	—
10	9	229	9110R		4713, 5713	DS0908BFD2, DS0908BFD5, DS0908BFD25	RB1010T05
10	12	305	12110R		5714	—	RBSA121014T05, RB1210T05
14	6	152	6114R		4782	DS0414BF5, DS0614BF2, DS0614BF5, DS0614BF25	RBPB65014T05, RBAE61115T05, RBAE6501115T05
14	9	229	9114R		4787, 5787	DS0914BF5	RBPB125014T05, RBAE91115T05, RBAE9501115T05
14	12	305	12114R		5794	DS1214BF5	RBAE121115T05, RBAE12501115T05, RBPB125014T05
14	3-5/8	92	314RC		5161, 5162	—	—
14	4	102	414R		5181	—	RB414T05
14	6	152	614R		5182, 4182,	—	RB65014T05, RB64214T05, RBWP64214T05, RB614T05
14	8	203	814R		5187, 4182, 7187	—	RB814, RBMC814
14	9	225	9514R		—	—	RBWP94214T05
12/16	9	229	9126R		—	—	—
12/16	12	305	12126R		—	—	—
18	6	152	6118R		4784, 5784	—	RB65018T05, RBAE61521T05, RBAE6501521T05,
18	9	229	9118R		4788, 5790, 5788	—	RBSA818T05, RBAE91521T05, RBAE9501521T05,
18	12	305	12118R		4789, 5791, 8789, 5789	—	RBSA1218T05, RBAE121521T05, RBAE12501521T05,
18	3-5/8	92	318RC		5163	—	RB318ST05, RB318ST50
18	4	102	418R		5183	—	—
18	6	152	618R		4184, 5184	—	RB64218T05, RB618T05, RBWP64218T05
18	8	203	818R		4188, 5188	—	RB94218T05, RB918T05, RB818T05
18	12	305	118R		5189	—	RB124218T05, RB1018T05, RB1218T05
24	6	152	624R		4186, 5186, 8186	—	RB64224T05, RB624T05
24	8	203	824R		—	DS0920BF2, DS0920BF5, DS0920BF25	—
10	6	152	610R		5090, 5091, 4091, 5092	—	RBWP64210T05, RB610T05
10	8	203	810R		4093, 5093	DS0914BGP2, DS-0914BGP5, DS0914BGP25	RBWP94210T05, RB810T05
10/14	6	152	650R		—	—	RB41014T05, RB61014T05, RB6501014T05, RB6501014TT05
10/14	8	203	850R		5193	DS0914AFC2, DS0914AFC5	RB81014C2, RB850812T05, RB81014T05, RB8501014T05
10/14	12	305	110R		5094, 5194	DS1214AFC5	RB125010T05, RB12551014T05, RB121014T05, RB12501014STT05
4	6	152	634R		—	—	—
6	6	152	656R		5035	DS0612BW2, DS0612BW5, DS0612BW25	RB63506T05, RB65006T05, RB65058T05
6	6	152	676RC		1606, 5041	—	RB65006CT05, RB65006CT50
6	9	229	956R		5016, 5036	DS0912BW2, DS0912BW5, DS0912BW25	RB95006C2, RB93506T05, RB95006T05
6	12	305	156R		5017, 5037	DS1212BW2, DS1212BW5, DS1212BW25	RB123506T05, RB125006T05
6	6	152	6W6R		1301, 1303, 1304, 1305, 7015, 7016	—	—
6	9	229	9W6R		—	DS0905FG, DS0905FG5, DS1205FG, DS1205FG5	—
6	6	152	636RP		—	—	RB65006PT05
GRIT	9	225	800DTDG		1450	DS0930DGX	RB0930C
GRIT	11	275	100DTDG		—	—	—
Grit	6	152	600RG		1421, 6430, 1420	—	RTCG6
Grit	8	203	800RG		1431, 6430, 1430	—	RTCG8
Grit	10	254	100RG		—	—	—

Diablo is a registered trademark of Freud America, Inc., which has not endorsed or approved this comparison.
The M.K. Morse Company has not endorsed or approved this comparison.



MASTER-BAND™ BLADES

MAXIMUM PERFORMANCE FOR PORTABLE BAND SAWS

ENHANCED BEAM STRENGTH

Specially treated bands of .023 and .025 thicknesses offer increased blade strength, reducing deflection and twisting of blades

SHATTER RESISTANT

Bi-Metal blades are designed to bend and resist breaking and extend blade life

LONG LASTING

LENOX TUFF TOOTH® design reinforces tooth for long blade life



TPI	LENGTH X WIDTH X THICKNESS		EDGE	3-PACK	25-PACK	APPLICATION
	IN	MM	MATERIAL	PROD NO	PROD NO	
10/14	44-7/8 x 1/2 x .023	1140 x 12.7 x .6	Matrix	8011438EW1014	9403B38EW1014	1/4" & larger, most metals
14	44-7/8 x 1/2 x .023	1140 x 12.7 x .6	Matrix	8011538EW14	9404B38EW14	3/16" – 3/8," most metals
14/18	44-7/8 x 1/2 x .023	1140 x 12.7 x .6	Matrix	8011238EW1418	9407B38EW1418	1/8" – 5/16," most metals
18	44-7/8 x 1/2 x .023	1140 x 12.7 x .6	Matrix	8011638EW18	9405B38EW18	3/32" – 1/4," most metals
24	44-7/8 x 1/2 x .023	1140 x 12.7 x .6	Matrix	8011738EW24	—	up to 1/8," most metals
10/14	44-7/8 x 1/2 x .025	1140 x 12.7 x .6	M42	80144385EW1014	9399B385EW1014	1/4" & larger, metals, including stainless steel
14	44-7/8 x 1/2 x .025	1140 x 12.7 x .6	M42	80145385EW14	—	3/16" – 3/8," metals, including stainless steel
14/18	44-7/8 x 1/2 x .025	1140 x 12.7 x .6	M42	80142385EW1418	9401B385EW1418	1/8" – 5/16," metals, including stainless steel
18	44-7/8 x 1/2 x .025	1140 x 12.7 x .6	M42	82310385EW18	9402B385EW18	3/32" – 1/4," metals, including stainless steel

WOLF-BAND® BLADES

PROFESSIONAL PERFORMANCE AND EXCEPTIONAL VALUE

LONG LASTING

High speed steel teeth provide a strong, long lasting cutting edge

SHATTER RESISTANT

Bi-Metal blades bend and resist breaking and extend blade life

EXCEPTIONAL VALUE

Professional performance and competitive pricing provide extraordinary cost-per-cut value



TPI	LENGTH X WIDTH X THICKNESS		3-PACK	5-PACK	25-PACK	APPLICATION
	IN	MM	PROD NO	PROD NO	PROD NO	
10/14	44-7/8 X 1/2 X .020	1140 X 12.7 X .5	—	8009838PW10145	3842338PW1014	1/4" (6 mm) & LARGER
14	44-7/8 X 1/2 X .020	1140 X 12.7 X .5	1208638PW143	8010738PW145	3842438PW14	3/16" (5 mm)–3/8" (10 mm)
14/18	44-7/8 X 1/2 X .020	1140 X 12.7 X .5	—	8009938PW14185	3842738PW1418	1/8" (3.2 mm)–5/16"
18	44-7/8 X 1/2 X .020	1140 X 12.7 X .5	1208838PW183	8010838PW185	3842538PW18	3/32" (2 mm)–1/4" (6 mm)
24	44-7/8 X 1/2 X .020	1140 X 12.7 X .5	1208938PW243	8010938PW245	3842638PW24	UP TO 1/8" (3.2 mm)
COMPACT PORTABLE BAND SAW BLADES						
10/14	35-3/8 X 1/2 X .020	900 X 13 X .50	—	1786673	1786678	1/4" (6 mm) & LARGER
14	35-3/8 X 1/2 X .020	900 X 13 X .50	—	1786674	—	3/16" (5 mm)–3/8" (10 mm)
18	35-3/8 X 1/2 X .020	900 X 13 X .50	—	1786675	1786680	3/32" (2 mm)–1/4" (6 mm)
24	35-3/8 X 1/2 X .020	900 X 13 X .50	—	1786676	—	UP TO 1/8" (3.2 mm)
SUB-COMPACT PORTABLE BAND SAW BLADES						
18	27-1/4 X 1/2 X .020	692.15 X 12.7 X .50	1910012*	*AVAILABLE IN 10 PACK ONLY		3/32" (2 mm)–1/4" (6 mm)
18	27 X 1/2 X .020	685.8 X 13 X .50	LXAPB27183	—	—	3/32" (2 mm)–1/4" (6 mm)