



Spears® Solvent Cement & Primer



ENGINEERING GUIDE

Contact Spears® for any Information not found.



Spears® Low VOC Solvent Cements, Primers & Accessories



Professional grade solvent cements developed for contractors, essential needs in joining PVC, CPVC and ABS pipe and fittings. Available in 1/4 pints, 1/2 pints, pints, quarts, gallons, and 5 gallons according to cement type. Spears® also offers a full assortment of daubers, swabs, rollers, brushes, cans and accessories.

All Low VOC for LEED® Credit

Environmentally friendly. LEED® Compliant (Leadership in Energy and Environmental Design). Credit can be gained through the use of Spears® Low VOC products. This program, developed by the US Green Building Council, uses SCAQMD Rule 1168 as a benchmark to qualify one credit toward LEED® certification for green building. Certified to GREENGUARD GOLD to Underwriters Laboratories (UL) 2818. UL GREENGUARD GOLD Certification allows for LEED® (Leadership in Energy and Environmental Design) credit eligibility.

NSF® Certified & Listed

Listed for use in piping applications such as potable water, turf, irrigation, pool & spa, industrial, plumbing, DWV, and/or sewer plus special applications including fire protection, chemical waste, and ultra-pure water. Certified as applicable to the Uniform Plumbing Code (NSF® U.P.Code) and CSA B181.2 B137.3 requirements - see specific listings.

Certified to ASTM Standards

Certified by NSF International to ASTM D 2564 for PVC Solvent Cements, F 493 for CPVC Solvent Cements, D 2235 for ABS Solvent Cements, D 3138 for ABS To PVC Solvent Cements and F 656 for Primers.

Cements for Specialty Systems

Specialty Cements formulated for special systems such as Copper Tube Size (CTS) Hot & Cold Water Distribution Systems, LabWaste® CPVC Corrosive Waste Drainage Systems, FlameGuard® CPVC Fire Sprinkler Systems, and Low Extractable PVC Ultra High Purity Water Systems.

Plus, special CPVC cements are specially formulated for use with Spears® ABS Type Approved and USCG Approved Pipe & Fittings for Marine Applications.

Cements for Special Applications

Solvent cements specially formulated for a variety of environmental applications. Such as POOL-PRO™ for PVC Pool & Spa applications, Wet-N-Dry for other PVC high moisture conditions, CPVC-24 the most Chemically Resistant cement available for both CPVC & PVC chemical applications, Transition cement for ABS to PVC, Multi-Purpose cement for use on PVC, CPVC, ABS & Styrene, and Hot Blue cement for PVC installation in challenging conditions including wet, damp or cold temperatures requiring rapid set and fast drying.

Notice: One-Step Cements are limited to applicable sizes. See Specific On-Step Cement for limitations.

Progressive Products From Spears® Innovation & Technology



Solvent Cements Technical

Spears® Solvent Cement & Primer

QUICK VIEW SELECTION GUIDE

Type	Body	Spears®/IPS Cross Reference		Color	Relative Set	Capacity	Features
		Spears®	IPS				
PVC	Regular	PVC-00	700	Clear	Fast	Schedule 40 - 4"	
		PVC-02	702	Clear	Fast	Schedule 40 - 4"	Dries Clearest, slightly thicker than PVC-00
	Medium	PVC-05	705 (Not in Gray)	Clear/ Grey	Fast	All Classes & Schedule 40 - 6" Schedule 80 - 4"	Industrial Duty Primerless Capability ¹
		PVC-21	721	Blue	Fast	Schedule 40 - 6" Schedule 80 - 4"	Primerless Capability ¹
	Heavy	PVC-11	711	Grey	Medium	All Classes & Schedules - 12"	Industrial Duty
		PVC-17	717	Clear Grey	Medium	All Classes & Schedules - 12" Non-pressure - 18"	Industrial Duty
	Extra Heavy	PVC-19	719	White/ Grey	Slow	All Classes & Schedules Requiring High Gap Filling - 30"	Industrial Duty
	Specialty Cements	PVC-25	725	Aqua Blue	Very Fast	All Classes & Schedules 40 - 6" Schedule 80 - 4"	Wet-N-Dry Formulations Primerless Capability ¹
		PVC-26	747	Blue	Very Fast	All Classes & Schedules 40 - 6" Schedule 80 - 4"	POOL-PRO™ Formulation for Pool & Spa Primerless Capability ¹ . Fades to clears as it cures.
		PVC-27	727	Clear	Very Fast	All Classes & Schedules - 40 - 6" Schedule 80 - 4"	Cold-N-Hot Formulation -15°F to 110°F Primerless Capability ¹
		PVC-37	737	Blue	Very Fast	All Classes & Schedules - 6" Schedule 80 - 4"	Formulated for Wet Conditions Primerless Capability ¹
		PVC-50	750	Blue	Very Fast	Schedule 40 - 6" Schedule 80 - 4"	HOT PVC Formulated Primerless Capability ¹
		PVC-95	795	Clear/Blue	Fast	All Classes & Schedule 40 - 6" Schedule 80 - 4"	Flexible PVC for Flex-Flex, Flex-Rigid Joints
		LX-5	N/A	Clear	Fast	Low Extractable PVC Systems - 6" Not to Exceed 6"	One Step ² Low Extractable, High Purity Cement
CPVC	Heavy	CPVC-24	724	Gray/ Orange	Medium	All Classes & Schedules PVC or CPVC - All Sizes	Most versatile, Chemically Resistant Cement for both PVC & CPVC Systems - including Duct - Industrial Duty
		Marine-24	N/A	Gray	Medium	All Schedules CPVC Marine Pressure Systems 1/2" - 12" For Use In Joining EverTUFF® Marine only	Cement for CPVC Marine Duty Pressure Systems
	Specialty Cements	LW-5	N/A	Mustard	Medium	LabWaste® Drainage Systems - 24" For Use In Joining LabWaste® only	One Step ² Cement-Only LabWaste® System Chemically Approved Cement
		OT-5	N/A	Mustard	Medium	OceanTUFF™ CPVC Black & Gray Drainage Systems - 12" For Use In Joining OceanTUFF™ only	One-Step ² Cement Only OceanTUFF™ System Chemically Approved Cement
		FS-5	N/A	Red	Fast	CPVC Fire Sprinkler Systems - Not to Exceed 3"	One-Step ² Cement for all CPVC Fire Sprinkler Systems
		CTS-5	FlowGuard Gold®	Yellow	Fast	CTS CPVC Systems - Not to Exceed 2"	One-Step ² Cement for all CTS CPVC Systems
ABS	Medium	ABS-71	771	Yellow/Milky	Fast	All ABS Classes & Schedules - 8"	
		ABS-73	773	Black	Fast	All ABS Classes & Schedules - 8"	
Transition & Multipurpose	Medium	ABS to PVC-94	794	Green	Fast	All Classes & Schedules - 6" (Except Schedule 80)	For ABS-to-PVC Transition Joints
		MULTI- PURPOSE	790	Clear	Fast	All Classes & Schedules - 6" Schedule 80 - 4"	For PVC and CPVC pressure ABS and Styrene low-pressure systems
Primers & Cleaners		Primer-75	P-75	Aqua Blue		All Classes, Schedules & Sizes; PVC & CPVC	Formulated for Wet Conditions Industrial Duty
		Primer21-70	P-70	Purple/Clear		All Classes, Schedules & Sizes; PVC & CPVC	Industrial Duty
		Primer21-68	P-68	Purple/Clear		All Classes, Schedules & Sizes; PVC & CPVC	
		Cleaner-65	C-65	Clear		All Classes, Schedules & Sizes; PVC & CPVC	For PVC, CPVC, ABS or Styrene
		Primer Cleaner-64	PC-64	Purple		All Classes, Schedules & Sizes; PVC & CPVC	

Notes:

1 = Primerless Capability indicates a cement can be used without primer in certain applications if local code permits. See specific cement information for further restrictions.

2 = One Step designates a cement specifically designed for use without primer. CTS One Step acceptability depends on local code requirements. CTS = Copper Tube Size, ASTM D2846 Hot and Cold Water Distribution System.



Low VOC PVC Cements

Regular, medium, heavy and extra heavy bodied cements are specifically formulated for PVC pipe in virtually every schedule and in sizes with interference fit to 30" diameter.

- Low VOC emissions comply with SCAQMD Rule 1168/316A
- 3-Year Shelf Life

PVC SOLVENT CEMENTS	Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
 PVC-00 CLEAR Regular bodied. Excellent for plumbing, DWV, irrigation, electrical conduit pool & spa and PVC foam core pipe.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 4" - All Classes and Schedules (except Schedule 80)	Fast	CLEAR	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	---
 PVC-02 CLEAR Regular bodied. Excellent for plumbing, DWV, irrigation, electrical conduit pool & spa and PVC foam core pipe.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 4" - All Classes and Schedules (except Schedule 80)	Fast	CLEAR	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Dries Clearest slightly thicker than PVC-00
 PVC-05 CLEAR/GRAY Medium bodied. Designed for Industrial, plumbing, DWV, irrigation, electrical conduit pool & spa and PVC foam core pipe.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 6" - All Classes and Schedules • 4" - Schedule 80	Fast	CLEAR	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Industrial Duty Primerless Capability ¹
 PVC-21 BLUE Medium bodied. High strength PVC cement suitable for use on rigid PVC. [†]	1/4 Pint 1/2 Pint Pint Quart Gallon	• 6" - Schedule 40 • 4" - Schedule 80	Fast	BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Primerless Capability ¹
 PVC-11 - GRAY Heavy bodied. Medium set allows more working time in warm weather and has good gap filling properties.	1/2 Pint Pint Quart Gallon	• 12" - All Classes & Schedules	Medium	GRAY	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code, CSA B137.3, B181.2 UL 2818	Industrial Duty
 PVC-17 CLEAR/GRAY Heavy bodied. Medium set allows more working time in warm weather and has good gap filling properties. Designed for plumbing, industrial, pool, irrigation and electrical piping systems.	1/2 Pint Pint Quart Gallon	• 12" - All Classes & Schedules • 18" - Non-Pressure	Medium	CLEAR/GRAY	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code (Clear/Gray) UL 2818 CSA B137.3, B181.2 (Gray only)	Industrial Duty
 PVC-19 WHITE/GRAY Extra Heavy bodied. Designed for large size piping systems requiring high gap filling properties such as industrial piping and fitting fabrication in pressure and non-pressure applications.	Pint Quart Gallon (F-Type & Paint Type) 5 Gallon	• 30" - All Classes & Schedules Requiring High Gap Filling	Slow	WHITE/GRAY	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818 CSA B137.3, B181.2 (Gray Only)	Industrial Duty

Notes

¹ = Primerless Capability indicates a cement can be used without primer in certain applications if local code permits

[†] = Can be used without primer on PVC Schedule 40 and SDR pressure water piping systems if local code permits. Do not use PVC-21 without primer in any other application, schedule, or size such as Schedule 80 industrial applications.

* = Contact Spears® for special packaging not listed.



Solvent Cements Technical

Spears® Solvent Cement & Primer

PVC SPECIALTY SOLVENT CEMENTS	Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
 PVC-25 AQUA BLUE WET-N-DRY Medium bodied. Formulated for wet conditions and quick pressurization. Designed for irrigation, plumbing, and pool & spa applications.	1/4 Pint 1/2 Pint Pint Quart Gallon	6" - All Classes and Schedules 4" - Schedule 80	Very Fast	AQUA BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Wet-N-Dry Formulation Primerless Capability ¹
 PVC-26 POOL-PRO™ BLUE Medium bodied. Formulated specifically for wet conditions in pool & spa applications. Fades to clear as it cures.	1/4 Pint 1/2 Pint Pint Quart Gallon	6" - All Classes and Schedules 4" - Schedule 80	Very Fast	BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Pool & Spa Formulation Primerless Capability ¹
 PVC-27 CLEAR COLD-N-HOT Medium bodied. Designed for industrial, plumbing, irrigation, pool & spa, electrical conduit and PVC foam core pipe.	Pint Quart Gallon	6" - All Classes and Schedules 4" - Schedule 80	Very Fast	CLEAR	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Cold-N-H Formulation -15°F to 110°F Primerless Capability ¹
 PVC-37 EverTUFF® TURF™ BLUE Medium bodied. Designed with slightly higher viscosity for use with demanding Turf, Agriculture and Well Casing applications. Formulated for wet conditions and quick pressurization. Fades to clear in sunlight.	1/4 Pint 1/2 Pint Pint Quart Gallon	6" - All Classes and Schedules 4" - Schedule 80	Very Fast	BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Formulated for Wet Conditions Primerless Capability ¹
 PVC-50 HOT BLUE Medium bodied. Excellent for use in challenging conditions including wet damp or cold temperatures in irrigation, plumbing DWV, pool & spa, and non-pressure applications. PVC-50 may be used without primer on Schedule 40 pipe and fittings if local code permits.	1/4 Pint 1/2 Pint Pint Quart Gallon	6" - Schedule 40 4" - Schedule 80	Very Fast	BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	HOT PVC Formulation Primerless Capability ¹
 PVC-95 CLEAR/BLUE Flexible Medium bodied. Specially formulated for use on flex-to-flex and flex-to-rigid PVC connections. Maintains high-strength, flexible joints.	1/4 Pint 1/2 Pint Pint Quart Gallon	6" - All Classes and Schedules 3" - Schedule 80	Fast	CLEAR/BLUE	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	Flexible PVC for Flex-Flex, Flex-Rigid Joints
 LX-5 CLEAR Low Extractable One-Step Cement. Specifically formulated for use with Spears® Low Extractable PVC piping. Unlike conventional PVC solvent cements, LX-5 contains fewer contaminants and cures quickly to reduce potential for TOC contamination. Maximum 6" size.	Pint Quart	6" - Low Extractable PVC Systems	Fast	CLEAR	ASTM D2564, NSF®-PW, DWV, SW, U.P. Code UL 2818	One Step ² Low Extractable, High Purity Cement

Notes

1 = Primerless Capability indicates a cement can be used without primer in certain applications if local code permits

2 = One Step designates a cement specifically designed for use without primer.

* = Contact Spears® for special packaging not listed.

CPVC Low VOC Cements

Heavy bodied cements are specifically formulated for CPVC plastic pipe and fittings including a variety of One-Step (no primer required) CPVC specialty cements. These products are ideal for use in hot/cold water plumbing systems, water treatment and chemical plants, as well as industrial piping systems.

Notice: One-Step Cements are limited to applicable sizes. See Specific On-Step Cement for limitations.

- Low VOC emissions comply with SCAQMD Rule 1168/316A
- 2-Year Shelf Life

CPVC SOLVENT CEMENTS	Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
 CPVC-24 GRAY/ORANGE Heavy bodied. High-strength, chemical-resistant solvent cement for use with CPVC piping systems carrying acids, bases, salts, and sodium hypochlorite. Ideal for use in waste water plants. Recommended for use on PVC industrial piping systems for chemical applications; best choice for both PVC and CPVC fume & air duct systems.	1/4 Pint 1/2 Pint Pint Quart Gallon	24" - All classes and schedules PVC or CPVC - All Sizes	Medium	GRAY/ORANGE	ASTM F493, NSF®-PW, DWV, SW, U.P. Code UL 2818	Most Versatile, Chemically Resistant Cement for both CPVC & PVC Systems - including Duct - Industrial Duty

Notes

* = Contact Spears® for special packaging not listed.

Solvent Cements Technical

Spears® Solvent Cement & Primer



CPVC SPECIALTY SOLVENT CEMENTS	Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
 LW-5 MUSTARD One-Step CPVC cement specifically formulated and approved for use with Spears® LabWaste® CPVC Corrosive Waste Drainage System Products. For use in joining LabWaste® only.	Pint Quart Gallon 5 Gallon	• 24" - LabWaste® Drainages Systems	Medium	MUSTARD	ASTM F493, NSF®-CW, PW, DWV, SW, U.P. Code, ICC-ES PMG UL 2818	One Step ¹ Cement - Only LabWaste® System Chemically Approved Cement
 OT-5 MUSTARD One-Step CPVC cement specifically formulated and approved for use with Spears® OceanTUFF™ ABS Type Approved & USCG Approved CPVC Drainage System Products for the Marine Applications. For use in joining OceanTUFF™ only.	Quart Gallon	• 12" - OceanTUFF™ CPVC Drainages Systems	Medium	MUSTARD	ASTM F493, NSF®-CW, PW, DWV, SW, U.P. Code, ICC-ES PMG UL 2818	One Step ¹ Cement - Only Approved Cement for use with Spears® OceanTUFF™
 FS-5 RED One-Step CPVC Cement specifically formulated and approved for use with Spears® FlameGuard® and other approved CPVC Fire Sprinkler Products. Maximum 3" size	Pint Quart	• 3" - CPVC Fire Sprinkler Systems	Fast	RED	ASTM F493, NSF®-PW, DWV, SW, U.P. Code, UL® FM® Approved UL 2818	One Step ¹ Cement for all CPVC Fire Sprinkler Systems
 CTS-5 EverTUFF® YELLOW Medium bodied. Cement for copper tube size pipe and fittings. Maximum 2" size for One - Step.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 4" - All classes and schedules (except Schedule 80)	Fast	YELLOW	ASTM F493/D2846, NSF®-PW, DWV, SW, U.P. Code, CSA B137.6, B181.2 UL 2818	One Step ¹ Cement for all CTS CPVC Systems
 MARINE-24 GRAY Heavy Bodied, High-strength, chemical resistant solvent cement for use with Spears® OceanTUFF™ ABS Type Approved & USCG Approved CPVC Presure Piping System Products for Marine Applications. For use in joining OceanTUFF™ only.	Quart Gallon	• 12" - Schedule 40 or 80 CPVC Marine Pressure Piping Systems CPVC Drainages Systems	Medium	MUSTARD	ASTM F493, NSF®-PW, DWV, SW, U.P. Code UL 2818	One Step ¹ Cement - Only Approved Cement for use with Spears® OceanTUFF™
Notes 1 = One Step designates a cement specifically designed for use without primer. CTS One Step acceptability depends on local code requirements. CTS = Copper Tube Size, ASTM D2846 Hot and Cold Water Distribution Systems * = Contact Spears® for special packaging not listed.						

ABS Low VOC Cements

ABS cements are specially formulated for rigid ABS pipe and fittings in all classes, schedules and fittings having interference type sockets. These medium-bodied, fast setting cements are used for all classes and schedules with interference fit through 8" diameter in ABS drain, waste and vent systems (DWV), and sewer applications. Do not use primer on ABS pipe and fittings.

- Low VOC emissions comply with SCAQMD Rule 1168/316A
- 3-Year Shelf Life

ABS SOLVENT CEMENTS	Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
 ABS-71 YELLOW/MILKY Medium bodied. ABS solvent cement for all classes and schedules of pipe and fittings.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 8" - All ABS Classes & Schedules	Fast	YELLOW/ MILKY	ASTM D2235, NSF®-DWV, SW, U.P. Code CSA (Yellow Only) B181.1 UL 2818	---
 ABS-73 BLACK Medium bodied. ABS solvent cement for all classes and schedules of pipe and fittings.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 8" - All ABS Classes & Schedules	Fast	BLACK	ASTM D2235, NSF®-DWV, SW, U.P. Code UL 2818	---
Notes * = Contact Spears® for special packaging not listed.						



Solvent Cements Technical

Spears® Solvent Cement & Primer

ABS to PVC Transition & Multi Purpose Low VOC Cements

Designed for joining PVC, ABS, CPVC and Styrene pipe and fittings; involving both similar materials and transition joints between dissimilar plastic materials.

- Low VOC emissions comply with SCAQMD Rule 1168/316A
- 3-Year Shelf Life

TRANSITION & MULTI-PURPOSE SOLVENT CEMENTS		Std. Pkg.*	Pipe Size	Set Time	Available Color	Industry Listing	Features
	ABS TO PVC-94 ABS-PVC GREEN Medium bodied. Specifically designed for use on ABS to PVC transition joints in non-pressure systems. Suitable for sewer and DWV applications.	1/4 Pint 1/2 Pint Pint Quart Gallon	• 6" - All Classes & Schedules (Except Schedule 80)	Fast	GREEN	ASTM D3138, NSF®-DWV, SW, U.P. Code UL 2818	For ABS-to-PVC Transition Joints
	MP-90 MULTI-PURPOSE CLEAR Medium bodied. High-strength cement for PVC and CPVC pressure and on ABS and styrene low-pressure systems.	1/2 Pint Pint Quart	• 6" - All Classes & Schedules • 6" - Schedule 80	Fast	CLEAR	Meets ASTM D2564, D2235, & F493 UL 2818	For PVC and CPVC pressure ABS and Styrene low-pressure systems

Notes
* = Contact Spears® for special packaging not listed.

Low VOC Solvent Primers & Cleaners

Primers are used for the surface preparation of plastic pipe and fittings, which is necessary for the proper solvent welding of these materials. Cleaner aids in pre-cleaning to remove oil and grease.

- All Spears® Primers and Cleaners are low VOC products, which are environmentally friendly with lower emissions and reduced odor, surpassing the most stringent regulations and comply with SCAQMD Rule 1168/316A.
- Spears® Primers are certified for use with potable water by NSF International.
- 3-Year Shelf Life

PRIMERS & CLEANERS		Std. Pkg.*	Available Color	Industry Listing	Features
	PRIMER-75 AQUA BLUE WET-N-DRY Fast acting industrial strength primer essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. Formulated for wet conditions and quick pressurization in Turf, Agriculture, Pool & Spa applications.	1/4 Pint 1/2 Pint Pint Quart Gallon	AQUA BLU	ASTM F656, NSF®-PW, DWV, SW UL 2818	Formulated for Wet Conditions Industrial Duty
	PRIMER-70 INDUSTRIAL GRADE PURPLE/CLEAR Premium, industrial strength primer essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. Specially recommended for use on Schedule 80 (150 psi and higher) and large size pipe. Excellent for cold weather applications.	1/4 Pint 1/2 Pint Pint Quart Gallon	PURPLE/CLEAR	ASTM F656, NSF®-PW, DWV, SW UL 2818 U.P. Code (Purple Only).	Industrial Duty
	PRIMER-68 PURPLE/CLEAR Essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. Choose from Clear or Purple color which provides positive identification that a primer was used (check local code requirements).	1/4 Pint 1/2 Pint Pint Quart Gallon	PURPLE/CLEAR	ASTM F656, NSF®-PW, DWV, SW UL 2818 U.P. Code (Purple Only)	---
	CLEANER-65 CLEAR Water-thin cleaner recommended for use before priming of pipe and fittings to remove dirt oil and grease from the bonding surfaces of PVC, CPVC, ABS and Styrene.	1/4 Pint 1/2 Pint Pint Quart Gallon	CLEAR	UL 2818	For PVC, CPVC, ABS or Styrene
	PRIMER CLEANER-64 PURPLE Combination of Cleaner for removing grease, oil and dirt from the bonding surfaces & Primer for softening PVC & CPVC pipe and fitting surfaces for solvent cement welding.	1/4 Pint 1/2 Pint Pint Quart Gallon	PURPLE	UL 2818	---

Notes
* = Contact Spears® for special packaging not listed.