

TITAN FLOW CONTROL, INC.

"Y" Type Strainers

Cast & Ductile Iron



YS 12-CI
Class 250
Threaded
Sizes: 1/4 ~ 3"



YS 12-DI
Class 300
Threaded
Sizes: 1/4 ~ 3"



YS 58-CI
Class 125
Flanged
Sizes: 2 ~ 24"



YS 58-D-GG
WOG 300
Grooved
Sizes: 2 ~ 12"




YS 59-CI
Class 250
Flanged
Sizes: 2 ~ 12"

Bronze & Brass



YS 55-EB
YS 55-BZ
Class 125
Threaded
Sizes: 1/4 ~ 3"



YS 56-EB
YS 56-BZ
Class 125
Solder
Sizes: 1/4 ~ 3"




YS 52-AB
Class 250
Threaded
Sizes: 1/4 ~ 3"

Lead Free!*




YS 54-AB
Class 150
Flanged
Sizes: 2 ~ 12"

Carbon & Stainless Steel



YS 80T-SS
800 WOG
Threaded
Sizes: 1/4 ~ 3"



Available in
WC6
Alloy 20
316L

YS 81-CS
YS 81-SS
Class 600
Threaded
Sizes: 1/4 ~ 3"

YS 82-CS
YS 82-SS
Class 600
Socket Weld
Sizes: 1/4 ~ 3"


* Bolted Cover is standard on sizes 2 1/2" and 3" and is optional on size 2".



YS 61-CS
YS 61-SS
Class 150
Flanged
Sizes: 1/2 ~ 24"




YS 62-CS
YS 62-SS
Class 300
Flanged
Sizes: 1/2 ~ 12"



YS 63-CS
YS 63-SS
Class 300
Butt Weld
Sizes: 1/2 ~ 12"



YS 65-CS
YS 65-SS
Class 600
Butt Weld
Sizes: 1/2 ~ 12"



If we don't have
it - we'll help you
find it!

Titan Routinely
Stocks:

- Sizes 1/4" through 24"
- Pressure Classes 125 ~ 2500
- Standard Materials
- Exotic Materials
- All End Connections

TITAN FLOW CONTROL, INC.

"Y" Type Strainers

Carbon & Stainless Steel



**YS 64-CS
YS 64-SS**
Class 600
Flanged
Sizes: 1/2 ~ 12"



**YS 66-CS
YS 66-SS**
Class 900
Butt Weld
Sizes: 1 ~ 12"



**YS 67-CS
YS 67-SS**
Class 900
Butt Weld
Sizes: 2 ~ 10"



**YS 68-CS
YS 68-SS**
Class 1500
Flanged
Sizes: 2 ~ 8"

HIGH PRESSURE




**YS 69-CS
YS 69-SS**
Class 1500
Butt Weld
Sizes: 2 ~ 8"



**YS 70-CS
YS 70-SS**
Class 2500
Flanged
Sizes: 2 ~ 8"



**YS 71-CS
YS 71-SS**
Class 2500
Butt Weld
Sizes: 1 1/2 ~ 10"



**YS 83-CS
YS 83-SS**
Class 1500
Threaded
Sizes: 1/2 ~ 3"

**YS 84-CS
YS 84-SS**
Class 1500
Socket Weld
Sizes: 1/2 ~ 3"

Available in
Additional
Materials



**YS 86-CS
YS 86-SS**
Class 2500
Socket Weld
Sizes: 3/4 ~ 2"

**DID
YOU
KNOW**

In Addition To
Titan's **LEAD-FREE**
Options-

Titan Can Provide NSF/ASME And FDA Approved Coatings; Making
The Product Suitable For Potable Water Applications. Numerous
Options Are Available, Please Contact Us For More Details.



TITAN FLOW CONTROL, INC.

"Y" Type Strainers

Ductile Iron



YS 58N-DI
Class 150
Flanged
Sizes: 2 ~ 12"



YS 58U-DI
Class 150
Flanged
Sizes: 2 ~ 12"

**DID
YOU
KNOW**

Titan's NSF Strainer
are **UL CERTIFIED?**

Titan NSF Strainers are UL certified and listed per UL subject 321 for use in the United States and Canada. Standard units are tested and certified per NSF 61 and NSF 372. These Products are Suitable For Potable Water Applications. Please Contact Us For More Details.

NSF Approved

TITAN FLOW CONTROL, INC.

Press-connect Strainers

Naval Brass



YS 57NB
200 WOG
Press-To-Connect
Sizes: 1/2" ~ 2"



CV 37NB
200 WOG
Press-To-Connect
Sizes: 1/2" ~ 2"

**DID
YOU
KNOW**

Titan's Press-Connect
Products
are **NSF CERTIFIED?**

Titan's Press Connect Products are certified per NSF 61 and NSF 372. Press-Connect ends quick installation helps complete project up to 3 times faster than customary methods. Please Contact Us For More Details.

TITAN FLOW CONTROL, INC.

Basket Strainers (Simplex)

Cast Iron



BS 25-CI
Class 125
Threaded
Quick-Open Cover
Sizes: $\frac{3}{8}$ ~ 3"



BS 25F-CI
Class 125
Flanged
Quick-Open Cover
Sizes: 1 ~ 8"



BS 55-CI
Class 125
Flanged
Clamp Cover
Sizes: 2 ~ 12"

Available with
bolted and
clamped cover



BS 65-CI
Class 125
Flanged
Bolted Cover
Sizes: 2 ~ 12"

Carbon & Stainless Steel



BS 35-CS
BS 35-SS
Class 150/300
Threaded
Sizes: $\frac{3}{8}$ ~ 3"



BS 35F-CS
BS 35F-SS
Class 150
Flanged
Sizes: 1 ~ 8"



BS 85-CS
BS 85-SS
Class 150
Flanged
Sizes: 2 ~ 12"

Available with
bolted and
clamped cover



BS 86-CS
BS 86-SS
Class 300
Flanged
Sizes: 2 ~ 12"

Fiberglass & Aluminum Bronze



BS 87F-CS
BS 87F-SS
Class 150
Flanged
Sizes: 1 ~ 16"



BS 89-CS
BS 89-SS
Class 600
Flanged
Sizes: 2 ~ 12"

Optional Cover Designs

Most Basket Strainer models can be constructed with various cover designs including bolted, clamped, and hinged.



BS 55-FRP
Class 150
Flanged
Sizes: 4 ~ 20"



BS 95-AB
Class 150
Flanged
Sizes: 2 ~ 12"

TITAN FLOW CONTROL, INC.

Duplex Strainers

Cast Iron



DS 595-CI

Class 125
Threaded
Cast Iron
Sizes: 3/4 ~ 2 1/2"

DS 695-CI

Class 125
Flanged
Cast Iron
Sizes: 1 ~ 4"



DS 695-CI

Class 125
Flanged
Cast Iron
Sizes: 6 ~ 8"

Aluminum Bronze



DS 596-AB

Class 150
Threaded
Aluminum
Bronze
Sizes: 3/4 ~ 2 1/2"

DS 696-AB

Class 150
Flanged
Aluminum
Bronze
Sizes: 1 ~ 4"

Stainless & Carbon Steel



DS 596-CS/SS

Class 150
Threaded
Carbon Steel
Stainless Steel
Sizes: 3/4 ~ 2 1/2"

DS 696-CS/SS

Class 150
Flanged
Carbon Steel
Stainless Steel
Sizes: 1 ~ 4"



DS 696-CS

Class 150
Flanged
Carbon Steel
Sizes: 6 ~ 8"

DS 696-SS

Class 150
Flanged
Stainless Steel
Sizes: 6 ~ 8"



DS 796-CS/SS

Class 300
Threaded
Carbon Steel
Stainless Steel
Sizes: 3/4 ~ 3"

DS 896-CS/SS

Class 300
Flanged
Carbon Steel
Stainless Steel
Sizes: 1 ~ 4"

Pump Products



Tri-Flow Valve TF 21-CI

Class 125
Flanged
Cast Iron
Sizes: 2 ~ 20"



Suction Diffuser SD 22-CI

Class 125
Flanged
Cast Iron
Sizes: 2 x 1 1/4 ~ 18 x 18"

Ball Valves



BV 25-SS

Male x Female
3000 WOG
Full Port Sizes: 1/4 ~ 1 1/2"
Reduced Port Size: 2"



BV 60-BZ

600 WOG
Male x Female
Full Port Design
Sizes: 1/4 ~ 2"